





LEGEND OF ELECTRICAL SYMBOLS

SYMBOLS

D E S C R I P T I O N

	CEILING MOUNTED LIGHT FIXTURE
	WALL MOUNTED LIGHT FIXTURE 7'-6" ABOVE FIN. FLOOR
	CEILING MOUNTED FLUORESCENT LIGHT FIXTURE
	DUPLEX GROUNDING ELECTRICAL OUTLET 15A X 125V AT 12" ABOVE FIN. FLOOR
	DUPLEX GROUNDING OUTLET IN G.F. CIRCUIT 20A, 125V WITH WEATHER PROOF COVER
	DUPLEX GROUNDING ELECTRICAL OUTLET 15A X 125V AT 42" ABOVE FIN. FLOOR
	THREE WIRE POWER RECEPTACLE 50A, 250V WITH 3 # 6 T W IN 1" CONDUIT
	SINGLE POLE TOGGLE SWITCH 15A, 125V AT 4'-6" ABOVE FIN. FLOOR
	THREE-WAY MERCURY SWITCH 15A, 125V AT 4'-6" ABOVE FINISH FLOOR
	GROUND FAULT CIRCUIT INTERRUPTED
	WALL MOUNTED PANEL BOX FLUSH MOUNTED AT 5'-6" ABOVE FINISH FLOOR
	CONDUIT IN WALLS OR FLOOR
	NUMBERS AT LIGHTS AND OUTLETS INDICATES CIRCUIT NUMBER
	CEILING MOUNTED LIGHT FIXTURE W/ LIGHTS ATTACHED
	IRC 313: SMOKE DETECTOR INTERCONNECTED W/ BATTERY BACKUP
	SECURITY SPOTLIGHT
	EXHAUST FAN/LIGHT FIXTURE
	COMMUNICATIONS/NETWORK RECEPTACLE
	LED CEILING LIGHT FIXTURES